

Jekyll MathJax Embedding

_layouts\post.html MathJax Rendering 가 .

- post.html

layout: default

```
<header >
  <h1 class="post-title">{{ page.title }}</h1>
</header>
<div class="content">
  {% include post-meta.html post=page %}

  <div class="post-body">
    {{ content }}
    {% include post-tags.html post=page %}
  </div>

  {% include comments.html %}
  {% include related_posts.html %}
</div>
```

- MathJax Code ...

```
<script type="text/x-mathjax-config">
  MathJax.Hub.Config({tex2jax: {inlineMath: [['$','$'], ['\\(','\\)']]}});
</script>
<script type="text/javascript" async
  src="https://cdn.mathjax.org/mathjax/latest/MathJax.js?config=TeX-MML-AM_CHTML">
</script>
```

- .

layout: default

```
<header >
  <h1 class="post-title">{{ page.title }}</h1>
</header>
<script type="text/x-mathjax-config">
  MathJax.Hub.Config({tex2jax: {inlineMath: [['$','$'], ['\\(','\\)']]}});
</script>
<script type="text/javascript" async
  src="https://cdn.mathjax.org/mathjax/latest/MathJax.js?config=TeX-MML-AM_CHTML">
</script>
<div class="content">
  {% include post-meta.html post=page %}

  <div class="post-body">
    {{ content }}
    {% include post-tags.html post=page %}
```

</div>

```
{% include comments.html %}
{% include related_posts.html %}
</div>
```

8

`._config.yml` Markdown Processing Setting

```
kramdown:
  auto_ids:      true
  entity_output: as_char
  toc_levels:    1..6
  smart_quotes:  lsquo,rsquo,ldquo,rdquo
  input:          GFM
  hard_wrap:     false
  footnote_nr:   1
  show_warnings: false
  math_engine:   mathjax
  math_engine_opts:
  preview:       true
  preview_as_code: true
```

•

[[KaTeX Embedding]]